

Copyright, 2023, American Standard Adhesives, Inc.

All rights reserved. Copying and/or downloading the information in this document is allowed for the purpose of properly utilizing American Standard Adhesives (ASA) products provided that: (1) the information is copied in full with no changes unless prior consent is obtained from ASA, and (2) neither the copy nor the original is resold or distributed to make a profit.

## **SECTION 1: IDENTIFICATION**

Product code ASA-8126

Product class Glue stick based on EVA-copolymer

Intended use of the product Intended for industrial use with a hot melt equipment

**Supplier information** American Standard Adhesives, Inc.

5061 Brooks St. Ste B Montclair, CA 91763 USA

Toll Free: +1 877 272-4582 Fax: +1 866-232-1888

Email: Service@asaglue.com

## **SECTION 2: HAZARD(S) IDENTIFICATION**

Chemical hazard class Not classified as hazardous according to OSHA Hazard

Communication Standard 29 CFR 1910.1200.

Label elements

Signal wordsNot applicableSymbolsNot applicablePictogramsNot applicable

**Supplemental Information** Wear protective gear for hands, face, eyes, and clothing while

handling materials in a molten state. Avoid contact with molten

hot melt, pre-melter, or applicator tip. Avoid direct eye exposure to vapors. In case of eye/skin contact with molten material, immediately flush with cold water and cover with a clean dressing. Do not attempt to remove molten material. Have a burn treated by a physician. May cause thermal burns.



# **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

CHEMICAL NAME	CAS NO.	CONCENTRATION PERCENTAGE (%)
EVA (Ethylene Vinyl Acetate) copolymer	24937-78-8	40-60
Synthetic resin	64742-16-1	20-30
Rosinester	8050-26-8	15-25
PE Wax	9002-88-4	2-10
Paraffin Wax	64742-43-4	2-10

## **SECTION 4: FIRST AID MEASURES**

General information	No special measures r	eauired. If	vou feel unwell, seek

medical advice (show the label is possible).

**Inhalation** No need for first aid is anticipated. Non-molten glue is not

expected to have any adverse effects. If molten glue is inhaled, move to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical

advice.

**Skin Contact** Immediately flush skin with large amounts of cold water for at

least 15 minutes. DO NOT ATTEMPT TO REMOVE SOLIDIFIED MATERIAL. Cover affected area with a clean

dressing. Get immediate medical attention.

Eye Contact Non-molten glue is not expected to have any adverse effect. If

molten glue contacts the eye, rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention immediately.

**Ingestion** No special measures are necessary. If you feel unwell, seek

medical attention.

Most important symptoms and effects, both acute and delayed

Ingredients are of low toxicity in nature. If it does have effects,

it will be on the central nervous system.



Indication of any immediate medical attention and special treatment needed

If medical advice is needed, have product container label at hand.

#### **SECTION 5: FIRE-FIGHTING MEASURES**

Extinguishing Media Fire-fighting procedures

Use CO2, extinguishing powder or water spray. Fight larger

fires with water spray or alcohol-resistant foam.

Advice for Firefighters
Precautionary measures

**Protection during** 

firefighting

Exercise caution when fighting any chemical fire

Do not enter fire area without proper protective equipment,

Condition

including respiratory protection.

Hazardous decomposition or by-

products

<u>Substance</u>

Carbon monoxide During combustion
Carbon dioxide During combustion

## **SECTION 6: ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment, and emergency procedures

Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**Environmental precautions** 

Avoid release to the environment. Do not allow product to reach sewer system or open water. Prevent from spreading (e.g., by damming-in or oil barriers).

Methods and materials for containment and cleaning up

Absorb with liquid binding materials (sand, diatomite, acid binders, general-purpose binders, sawdust). Allow to solidify. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.



# **SECTION 7: HANDLING AND STORAGE**

**Precautions for safe handling**Ensure that suitable extractors/ventilation systems are

available on processing machines and in the workplace. Avoid contact with oxidizing agents (e.g. chlorine, chromic acid, etc.)

**Conditions for safe storage** Store in cool, dry place in tightly closed containers. No more

than 140 °F (60°C) ambient temperature. Avoid direct contact with sunlight or heat source. Store away from heat and

oxidizing agents.

## **SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters** 

Occupational exposure limits 
No occupational exposure limit values exist for any of the

components listed in Section 3 of this SDS.

Personal protective equipment

(PPE)

**Personal protective** 

equipment

The standard precautionary measures for handling chemicals should be observed. Wash hands before breaks and at the end of work. Avoid skin contact with the liquefied material.

**Respiratory protection** Not necessary if room is well-ventilated.

**Skin/hand protection** Not required.

**Eye/face protection** Select and use eye/face protection to prevent contact based

on the results of an exposure assessment. Full face shield and indirect vented goggles are recommended during refilling

and spraying.

**Thermal hazards** Wear heat insulating gloves when handling hot material to

prevent thermal burns.

# **SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

Information on basic physical and

chemical properties .

Appearance Stick Color Yellow

PH value

Odor None

**Specific Gravity** - [Ref std: Water = 1]



Solubility in water Insoluble

Vapor pressure (mmm Hg) - Vapor density -

Evaporation rate

 Flash Point
 536°F (280°C)

 Softening point
 198°F (92.22°C)

Auto-ignition Lower/upper flammable limits Flammability (solid, gas) Decomposition temperature Partition coefficient -

(n-octanol/water)

# **SECTION 10: STABILITY AND REACTIVITY**

Reactivity None known

**Chemical stability** Stable under recommended handling and storage conditions.

See Section 7.

**Possible hazardous reactions** The following conditions may increase the chance of fire and

explosion: static electricity, spark, fire, flammable material,

strong oxidant (e.g., peroxide, nitrate, perchlorate)

Conditions to avoid Prolong overheating

**Possible hazard reaction**Toxic fumes may be released if heated above the

decomposition point. No dangerous reactions known.

Hazardous decomposition

products

Carbon dioxide, carbon monoxide, and organic vapors.

#### **SECTION 11: TOXICOLOGICAL INFORMATION**

Information on toxicological

effects

Based on test data and/or information on the components, this material may produce the following health effects:

Signs and symptoms of exposure

Inhalation

No health effects are expected.

**Skin contact** During heating, contact with skin may lead to thermal burns that

include signs/symptoms of intense pain, redness, swelling, and

tissue destruction.



**Eye contact** During heating, contact with skin may lead to thermal burns that

include signs/symptoms of intense pain, redness, swelling, and

tissue destruction.

**Ingestion** No known health effects.

Additional toxicology information When used and handled according to specifications, the

product does not have any harmful effects according to our

experience and the information provided to us.

# **SECTION 12: ECOLOGICAL INFORMATION**

Aquatic toxicity No relevant information available

Persistence and degradability No relevant information available

Behavior in environmental

systems

No relevant information available

Results of PBT and vPvB

assessment

No relevant information available

Other adverse effects Avoid release to the environment

## **SECTION 13: DISPOSAL CONSIDERATIONS**

Sewage disposal recommendations

Do not dispose waste into sewer

**Waste disposal recommendation** Must not be disposed together with household garbage.

Dispose contents in accordance with the

local/regional/national/international regulations. Empty contaminated packaging thoroughly. They can be recycled after thorough and property cleaning. Packaging that cannot be cleaned are to be disposed off in the same manner as the

product.

Consult all relevant authorities and regulation prior to disposal to ensure proper classification. Use an approved industrial waste facility to dispose off waste products. As an alternative, an authorized waste incineration plan could be used as a method of disposal.



#### **SECTION 14: TRANSPORT INFORMATION**

In accordance with DOTNot regulated for transportIn accordance with IMDGNot regulated for transportIn accordance with IATANot regulated for transportIn accordance with TDGNot regulated for transport

These transportation categories are offered as a convenience to the customer.

YOU, the shipper, are still in charge of adhering to all rules and legislation that may be in force, including the right packaging and transportation classification.

The transportation classes used by American Standard Adhesives (ASA) are determined by the product compositions, packaging, corporate policies, and ASA's understanding of the relevant current regulations. The accuracy of this classification information is not guaranteed by ASA. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original ASA package is certified for U.S. ground and ocean shipment only. If you are shipping by air, please verify the applicable regulatory requirements.

## **SECTION 15: REGULATORY INFORMATION**

**US federal regulations**The components of this product are listed in the TSCA

Inventory.

**US state regulations**Neither this product or its chemical components appear on

any US state lists.

**Canadian regulations**The components of this product are on the DSL inventory or

are exempt from listing.

International regulations Contact American Standard Adhesives for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200



# **SECTION 16: OTHER INFORMATION**

Party responsible for the American Standard Adhesives, Inc. preparation of this document + 1 909 673-9898

As of the date of issuance, it the information provided in this Safety Data Sheet is accurate. To the best of our knowledge and after careful preparation, it is truthful and correct. The recommendations and information provided for this product are given with the assumption that the purchaser will independently evaluate them.

**DISCLAIMER**: This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which American Standard Adhesives (ASA) assumes legal responsibility. The data is submitted for the user's information and considerations only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws, and regulations.

As a service, ASA offers its information in electronic format. In the rare instance that electronic transfer may result in errors, omissions, or alterations in this information, ASA makes no guarantees as to its accuracy or completeness this document. Data retrieved directly from ASA will always be the most complete and up-to-date information.